

Technical Product Information Protection Paper P60+

Protection paper with *ultra-removable* adhesive, water impermeable

Description	
Self-adhesive universal cover and surface protection material based on a robust, tear-resistant kraft paper reinforced with a special layer and a substrate-friendly water based special adhesive. The product is impermeable for water and other liquids, but should not be exposed to wet conditions for extended time period.	
Application	
Protection Paper P60+ is ideally suited for easy and efficient protective covering in renovation or other DIY work or for transport protection. Due to easy roll-off the product can be applied quickly and convenient, even for covering large areas e.g. windowsills, radiators, handrails, furniture, etc. The well balanced special adhesive allows the application also on highly sensitive surfaces, such as wallpapers, veneers, sensitive wood surfaces or poorly adhering paints or colors.	
Application details	
Protection Paper P60+ provides excellent protection against paint splashes, dirt and dust. The product is also suitable for direct coating with paint or varnish. It resists and is impermeable for splashes of water and other liquids. Please pay attention that the paper should not be soaked through and should not be removed from substrate when it is wet. On smooth surfaces and upon removal directly after applying paint the product can serve as a painters tape. When applying on structured or non smooth surfaces the additional use of painters tape is recommended. The product is very easily removable from almost all surfaces without leaving residues and does not harm also most sensitive surfaces.	
Due to the large number of substrates, varnishes and conditions of use in practice, a trial application should always be carried out in an inconspicuous place in order to check the suitability. This is especially recommended before usage on natural or artificial stone.	
Max. application time	60 Days indoor on standard surfaces 14 Days on high-sensitive surfaces (e.g. paper, wallpapers)
Storage condition	10 - 30°C; 40 - 60 % rel. humidity, protected from light
storage stability @ 20°C, 50% R.H.	2 years
Technical data	
Backing material	Kraft paper white, reinforced with special layer Areal weight: 62 g/sqm
Adhesive	polyacrylate, waterborne, free of solvents
Thickness	75 µm
Peel adhesion	48 cN / 25 mm
Tensile strength	63 N / 15 mm

Warranty: AMC self-adhesive film and paper products are manufactured according to highest quality standards and pass stringent quality controls before shipment. The wide range of different applications does not allow to test all possibilities of employment.

All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For advice or technical support the AMC technical department will be pleased to assist.

Rev. 2.1; 11.30.2020

AMC AG - Division Global Notes / Division Print Inform, Robert-Bosch-Straße 1, 19230 Hagenow/Germany,
Tel. +49(0)3883 6195-0, Fax +49(0)3883 6195-550, E-Mail: info@globalnotes.de, www.globalnotes.de